



FAIR-PLAY SWIMMING SCOREBOARD

LANE PLACE		TIME	LANE PLACE		TIME
1	3	1:40.87	5	5	1:41.09
2	6	1:41.62	6	2	1:40.07
3	4	1:41.05	7	7	1:42.05
4	1	1:39.96	8	8	1:42.09

Model: **SW-1528-4**

DIMENSIONS:

HEIGHT:	4'-6"	LENGTH:	14'-0"	DEPTH:	4"	WEIGHT:	335 lbs.
----------------	-------	----------------	--------	---------------	----	----------------	----------

STANDARD EQUIPMENT:

- Energy efficient LED designs
- Three distinct LED digit colors to visually organize critical game information
- Heavy-duty, vibrating horn (103 dB)
- Free Help Desk Support
- Free project design renderings
- Factory authorized national and local sales, service and installation
- Choose from 10 durable paint colors
- Choose from 15 popular vinyl trim colors
- Over 75 years of sports scoring experience
- Sport-specific control console inserts
- HB-800 data connection kit
- Choice of Fair-Play's scorekeeper approved control systems*
- Changeable scoreboard game captions*
- 5-year limited warranty
- ETL/CETL listed to UL standard
- Convenient built-in service points for easy-access
- Durable, corrosion resistant aluminum construction
- Complete, safe and durable display mounting system

OPTIONAL EQUIPMENT:

- Custom paint and vinyl trim colors
- Personalized vinyl home team name
- Illuminated and non-illuminated identification and sponsorship signage
- Custom, unique signage options
- Programmable electronic team name message centers*
- Mono- or full-color electronic message display with Fair-Play's exclusive ProLine control system
- Carrying case for scoreboard console
- Wireless data transmission (includes receiver and transmitter)
- Portable, battery-operated scoreboard control
- Integrated, second operator statistics control*
- Fully-integrated or stand-alone shot and game timers Plug-and-play clock, shot time and horn hand switches
- Illuminated backboard goal lights
- Scorer's table with built-in BB-1600-4 scoreboard
- Synchronized locker room game / time of day clocks
- Protective net



OPERATING TEMPERATURES:

Scoreboard display: -22° to 131° Fahrenheit (-30° to 55° Celsius)

Control console: 32° to 131° Fahrenheit (0° to 55° Celsius)

OTHER DIMENSIONS:

CAPTIONS (H" x W")		DIGIT SIZES (H")	
LANE	4" x 12"	Lane	10"
PLACE	4" x 15"	Place	10"
TIME	4" x 11"	Time	10"
COLON DIAMETER	1.75"		
DECIMAL	1.75"		

ELECTRICAL	
Voltage	120 VAC
Hertz	60
Watts	404
Amps	4
Phase	1
Wiring	2-Wire + ground
Circuits Required	1
Safety Listing	ETL/CETL

Fair-Play offers 15 FREE standard trim tape colors



Fair-Play offers 12 FREE standard scoreboard colors. Custom colors available



Fair-Play by Trans-Lux Corporation

1700 Delaware Avenue • Des Moines, IA 50317 • 800.247.0265 • sales@fair-play.com • fair-play.com