

Retrofit Kit Strips 2x2 and 2x4

Features and Benefits

- 45 and 55 Watt Low Power and High Performance
- For easy field replacement, the LED strips are on replaceable circuit boards and screwed to twin aluminum 90-degree carrier angles set at 45-degrees, for added heat sinking and optic diffusion.
- 120-277V class 2 UL driver Included
- 45 deg. optic angle of each strip for beam spread
- 4 LED FR4 light strips for 2'x2' and 2'x4'
- 0-10V dimming standard
- All components are discrete parts allowing for sustainable repair and upgrade cycles
- Uses thermal dot technology for easy warranty control
- 1 x 1 x .06 aluminum angle carriers
- Sealed driver
- Completed wiring harness with Tyco quick connection plugs
- LED strips screwed to carrier angle for field replacement if needed
- < 3 pounds for easy handling over head
- Rated Lifetime: 50,000 hours at L70 standards
- 5 Year Warranty*
- UV, IR and Mercury-free



**5 Year
Warranty**

**Reduces
Energy & Cost**

**Rated Life
50,000 hours**

Part Number:	Wattage:	Description:	Lumens:	CRI:	CCT:	Beam Angle:
TLRKL23U4535	45	Retrofit kit linear strips universal voltage	3768	> 85	3500K	45°/90°
TLRKL23U4541	45	Retrofit kit linear strips universal voltage	3421	> 85	4100K	45°/90°
TLRKL23U4550	45	Retrofit kit linear strips universal voltage	3768	> 85	5000K	45°/90°
TLRKL23U4535DV	45	Dimming Retrofit kit linear strips universal voltage	3768	> 85	3500K	45°/90°
TLRKL23U4541DV	45	Dimming Retrofit kit linear strips universal voltage	3421	> 85	4100K	45°/90°
TLRKL23U4550DV	45	Dimming Retrofit kit linear strips universal voltage	3768	> 85	5000K	45°/90°
TLRKL45U5535	55	Retrofit kit linear strips universal voltage	4569	> 85	3500K	45°/90°
TLRKL45U5541	55	Retrofit kit linear strips universal voltage	4498	> 85	4100K	45°/90°
TLRKL45U5550	55	Retrofit kit linear strips universal voltage	4903	> 85	5000K	45°/90°
TLRKL45U5535DV	55	Dimming Retrofit kit linear strips universal voltage	4569	> 85	3500K	45°/90°
TLRKL45U5541DV	55	Dimming Retrofit kit linear strips universal voltage	4498	> 85	4100K	45°/90°
TLRKL45U5550DV	55	Dimming Retrofit kit linear strips universal voltage	4903	> 85	5000K	45°/90°

Applications

- Offices
- Lobbies
- Hallways
- Conference rooms
- Schools
- Airports
- Healthcare facilities
- Showrooms
- Corporate campuses
- Retailers

Voltage:	Dimensions (in inches):	Operating Life Hours:	Operating Frequency:	Operating Temperature:	Indoor/ Outdoor:	Certified Installer Required:
120-277V	22.5" x 1.5" x 2.5" 45" x 1.5" x 2.5"	50,000	50-60 Hz	-28 °C - 48 °C	Indoor	Yes



Certifications:
RUC, RUus

*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com