

1X Universal MINI21 Shoebox Kit

Features and Benefits

- 30, 40, 50 and 60 Watt Low Power and High Performance
- Multiple temperature control values
- Over temperature protection, shut down at critical temperature and resume operation temperature
- Under-voltage lockout for power off or brownout
- 0-10V Dimming compatible
- 0-10V Input Port
- Occupancy sensing Current accuracy over the LED operating temperature range +/- 3%
- Rated life 100,000 hours
- 10 Year Warranty*
- UV, IR and Mercury - free
- UL-Dry and Damp Location



10 Year Warranty

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Wattage:	Dimmable:	Lumens:	Voltage:	Life Hours:	Color Temperature(CCT):
GTP-UNVSB-1XM21	30	Yes	2679	120/277v	100,000	2700K - 5700K
GTP-UNVSB-1XM21	40	Yes	3742	120/277v	100,000	2700K - 5700K
GTP-UNVSB-1XM21	50	Yes	4594	120/277v	100,000	2700K - 5700K
GTP-UNVSB-1XM21	60	Yes	5910	120/277v	100,000	2700K - 5700K

Minimum Fixture Diameter:	Maximum Fixture Diameter:	Dimensions (in inches):	Operating Temperature:	Indoor/Outdoor:	Certified Installer Required:
14.4" x 11" inches	27.5" x 24" inches	11.5" x 8"	-40°C to 85°C	Both	Yes



Yoke Application Available

Applications

- Shoebox
- Highbay
- Cobrahead
- Canopy
- Parking Lot
- Lowbay
- Wall Pack

GTP-UNVSB - 1XM21 -

Mounting Options
1XM21 (1 module)

Color Temp.
GR (5700K)
BR (5000K)
YW (4100K)
BL (4000K)
RD (3500K)
PU (3000K)
OR (2700K)

Input Voltage
120/277 (v)
340/480 (v)

Output Setting
 [Ratings Per Module]
HO (60W, 5910lm)
HI (50W, 4594lm)
MH (40W, 3742lm)
ML (30W, 2679lm)

Optics
L2 (Type II)
L3 (Type III)
L10 (10 Degree)
L25 (25 Degree)
L50 (50 Degree)
L75 (75 Degree)
NL (No Optics)



Certifications:
RoHS, ETL Listed



*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
 300 N Elizabeth St Suite 610c
 Chicago, IL 60607
 800.559.8197 • www.Trans-Lux.com