

2X Universal Highbay Kit

Features and Benefits

- 150, 170, 190, and 270 Watt Low Power and High Performance
- Multiple temperature control values
- Over temperature protection, shut down at critical temperature and resume operation temperature
- Under-voltage lockout for power off or brownout
- 0-10 V Dimming compatible
- 0-10v Input Port
- Occupancy sensing Current accuracy over the LED operating temperature range +/- 3%
- Rated life 100,000 hours
- 10 Year Warranty*
- UV, IR and Mercury - free
- UL-Dry and Damp Location



10 Year Warranty

Reduces Energy & Cost

No Lead or Mercury



Yoke Application Available

Part Number:	Wattage:	Dimmable:	Lumens:	Voltage:	Life Hours:	Color Temperature(CCT):
GTP-UNVHB-2X5498	150	Yes	15628	120/277v	100,000	2700K - 5700K
GTP-UNVHB-2X5498	170	Yes	17998	120/277v	100,000	2700K - 5700K
GTP-UNVHB-2X5498	190	Yes	18894	120/277v	100,000	2700K - 5700K
GTP-UNVHB-2X5498	270	Yes	26328	120/277v	100,000	2700K - 5700K

Minimum Fixture Diameter:	Maximum Fixture Diameter:	Dimensions (in inches):	Operating Temperature:	Indoor/ Outdoor:	Certified Installer Required:
15" inches	28" inches	14.5" x 14.5"	-40° C to 85° C	Outdoor	Yes

Applications

- Cobrahead
- Shoebox
- Canopy
- Parking Lot
- Highbay
- Lowbay
- Wall Pack

GTP-UNVHB - 2X5498 -

Mounting Options
2X5498 (2 module)

Color Temp.
GR (5700K)
BR (5000K)
YW (4100K)
BL (4000K)
RD (3500K)
PU (3000K)
OR (2700K)

Input Voltage
120/277 (v)
340/480 (v)

Output Setting
 [Ratings Per Module]
HO (270W, 26328lm)
HI (190W, 18894lm)
MH (170W, 17998lm)
ML (150W, 15628lm)

Optics
L2 (Type II)
L3 (Type III)
L10 (10 Degree)
L25 (25 Degree)
L50 (50 Degree)
L75 (75 Degree)
NL (No Optics)



Certifications:
RoHS, ETL Listed

*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
 300 N Elizabeth St Suite 610c
 Chicago, IL 60607
 800.559.8197 • www.Trans-Lux.com