

10W 3ft TLSecond GEN T8 LED Tube

INDOOR
Linear Tube

Features and Benefits

- 10 Watt Low Power and High Performance
- Energy savings about 70%
- Unique aesthetics for commercial grade fixtures
- Excellent efficacies of up to 100 lm/W
- For Dimmable Tubes: 0-10V Dimming
- Available with internal and external drivers
- Rated Lifetime: 50,000 hours
- 5 Year Warranty*
- UV, IR and Mercury-free




5 Year Warranty

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Single End Tubes					
TL-T8-10W900 BINS30F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	3000K	900	≥83
TL-T8-10W900 BINS35F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	3500K	1000	≥83
TL-T8-10W900 BINS40F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	4000K	1000	≥83
TL-T8-10W900 BINS45F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	4500K	1000	≥83
TL-T8-10W900 BINS50F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	5000K	1000	≥83
Two End Tubes					
TL-T8-10W900 BINT30C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	3000K	900	≥83
TL-T8-10W900 BINT35C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	3500K	1000	≥83
TL-T8-10W900 BINT40C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	4000K	1000	≥83
TL-T8-10W900 BINT45C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	4500K	1000	≥83
TL-T8-10W900 BINT50C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	5000K	1000	≥83

Voltage:	Power Factor:	Operating Temperature:	Life Hours:	Case Quantity:	Dimensions (in inches):	Indoor/Outdoor:	Certified Installer Required:
100-277 VAC	> 0.9	-10 °C to 30 °C	50,000	25 pcs	36" x 1.3"	Indoor	Yes



Applications

- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail



Certifications:
RoHS, ETL Listed

*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com

10W 3ft TLSecond GEN T8 LED Tube

Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Two End Tubes					
TL-T8-10W900 BINT30F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	3000K	900	≥83
TL-T8-10W900 BINT35F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	3500K	1000	≥83
TL-T8-10W900 BINT40F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	4000K	1000	≥83
TL-T8-10W900 BINT45F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	4500K	1000	≥83
TL-T8-10W900 BINT50F	Frosted 3' 10 Watt T8 Tube, Internal Driver	No	5000K	1000	≥83
Two End Tubes					
TL-T8-10W900 BINT30C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	3000K	900	≥83
TL-T8-10W900 BINT35C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	3500K	1000	≥83
TL-T8-10W900 BINT40C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	4000K	1000	≥83
TL-T8-10W900 BINT45C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	4500K	1000	≥83
TL-T8-10W900 BINT50C	Clear 3' 10 Watt T8 Tube, Internal Driver	No	5000K	1000	≥83
Single End Tubes					
TL-T8-10W900 BIDS30F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	3000K	900	≥83
TL-T8-10W900 BIDS35F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	3500K	1000	≥83
TL-T8-10W900 BIDS40F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	4000K	1000	≥83
TL-T8-10W900 BIDS45F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	4500K	1000	≥83
TL-T8-10W900 BIDS50F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	5000K	1000	≥83
Single End Tubes					
TL-T8-10W900 BIDS30C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	3000K	900	≥83
TL-T8-10W900 BIDS35C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	3500K	1000	≥83
TL-T8-10W900 BIDS40C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	4000K	1000	≥83
TL-T8-10W900 BIDS45C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	4500K	1000	≥83
TL-T8-10W900 BIDS50C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	5000K	1000	≥83
Two End Tubes					
TL-T8-10W900 BIDT30F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	3000K	900	≥83
TL-T8-10W900 BIDT35F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	3500K	1000	≥83
TL-T8-10W900 BIDT40F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	4000K	1000	≥83
TL-T8-10W900 BIDT45F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	4500K	1000	≥83
TL-T8-10W900 BIDT50F	Frosted 3' 10 Watt T8 Tube, Internal Driver	Yes	5000K	1000	≥83
Two End Tubes					
TL-T8-10W900 BIDT30C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	3000K	900	≥83
TL-T8-10W900 BIDT35C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	3500K	1000	≥83
TL-T8-10W900 BIDT40C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	4000K	1000	≥83
TL-T8-10W900 BIDT45C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	4500K	1000	≥83
TL-T8-10W900 BIDT50C	Clear 3' 10 Watt T8 Tube, Internal Driver	Yes	5000K	1000	≥83