

31W 6ft TLSecond GEN T8 LED Tube

INDOOR
Linear Tube

Features and Benefits

- 31 Watt Low Power and High Performance
- Energy savings about 70%
- Unique aesthetics for commercial grade fixtures
- Excellent efficacies of up to 100 lm/W
- For Dimmable Tubes: 0-10V Dimming
- Available with internal and external drivers
- Rated Lifetime: 50,000 hours
- 5 Year Warranty*
- UV, IR and Mercury-free

**5 Year
Warranty**

**Reduces
Energy & Cost**

**No Lead or
Mercury**



Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Single End Tubes					
TL-T8-31W1800 BINS30C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	3000K	3250	≥80
TL-T8-31W1800 BINS35C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	3500K	3250	≥80
TL-T8-31W1800 BINS40C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	4000K	3300	≥80
TL-T8-31W1800 BINS45C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	4500K	3300	≥80
TL-T8-31W1800 BINS50C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	5000K	3350	≥80
Single End Tubes					
TL-T8-31W1800 BINS30F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	3000K	3250	≥80
TL-T8-31W1800 BINS35F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	3500K	3250	≥80
TL-T8-31W1800 BINS40F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	4000K	3300	≥80
TL-T8-31W1800 BINS45F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	4500K	3300	≥80
TL-T8-31W1800 BINS50F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BINT30C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	3000K	3250	≥80
TL-T8-31W1800 BINT35C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	3500K	3250	≥80
TL-T8-31W1800 BINT40C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	4000K	3300	≥80
TL-T8-31W1800 BINT45C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	4500K	3300	≥80
TL-T8-31W1800 BINT50C	Clear 6' 31 Watt T8 Tube, Internal Driver	No	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BINT30F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	3000K	3250	≥80
TL-T8-31W1800 BINT35F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	3500K	3250	≥80
TL-T8-31W1800 BINT40F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	4000K	3300	≥80
TL-T8-31W1800 BINT45F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	4500K	3300	≥80
TL-T8-31W1800 BINT50F	Frosted 6' 31 Watt T8 Tube, Internal Driver	No	5000K	3350	≥80

Applications


- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail

Voltage:	Power Factor:	Operating Temperature:	Life Hours:	Case Quantity:	Dimensions (in inches):	Indoor/Outdoor:	Certified Installer Required:
100-277 VAC	> 0.9	-10°C to 30°C	50,000	25 pcs	72" x 1.3"	Indoor	Yes

NOTE: Bold Part Numbers listed above are cUL



Certifications:
RoHS, FCC



*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com

31W 6ft TLSecond GEN T8LED Tube

Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Single End Tubes					
TL-T8-31W1800 BONS30C	Clear 6' 31 Watt T8 Tube, External Driver	No	3000K	3250	≥80
TL-T8-31W1800 BONS35C	Clear 6' 31 Watt T8 Tube, External Driver	No	3500K	3250	≥80
TL-T8-31W1800 BONS40C	Clear 6' 31 Watt T8 Tube, External Driver	No	4000K	3300	≥80
TL-T8-31W1800 BONS45C	Clear 6' 31 Watt T8 Tube, External Driver	No	4500K	3300	≥80
TL-T8-31W1800 BONS50C	Clear 6' 31 Watt T8 Tube, External Driver	No	5000K	3350	≥80
Single End Tubes					
TL-T8-31W1800 BONS30F	Frosted 6' 31 Watt T8 Tube, External Driver	No	3000K	3250	≥80
TL-T8-31W1800 BONS35F	Frosted 6' 31 Watt T8 Tube, External Driver	No	3500K	3250	≥80
TL-T8-31W1800 BONS40F	Frosted 6' 31 Watt T8 Tube, External Driver	No	4000K	3300	≥80
TL-T8-31W1800 BONS45F	Frosted 6' 31 Watt T8 Tube, External Driver	No	4500K	3300	≥80
TL-T8-31W1800 BONS50F	Frosted 6' 31 Watt T8 Tube, External Driver	No	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BONT30C	Clear 6' 31 Watt T8 Tube, External Driver	No	3000K	3250	≥80
TL-T8-31W1800 BONT35C	Clear 6' 31 Watt T8 Tube, External Driver	No	3500K	3250	≥80
TL-T8-31W1800 BONT40C	Clear 6' 31 Watt T8 Tube, External Driver	No	4000K	3300	≥80
TL-T8-31W1800 BONT45C	Clear 6' 31 Watt T8 Tube, External Driver	No	4500K	3300	≥80
TL-T8-31W1800 BONT50C	Clear 6' 31 Watt T8 Tube, External Driver	No	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BONT30F	Frosted 6' 31 Watt T8 Tube, External Driver	No	3000K	3250	≥80
TL-T8-31W1800 BONT35F	Frosted 6' 31 Watt T8 Tube, External Driver	No	3500K	3250	≥80
TL-T8-31W1800 BONT40F	Frosted 6' 31 Watt T8 Tube, External Driver	No	4000K	3300	≥80
TL-T8-31W1800 BONT45F	Frosted 6' 31 Watt T8 Tube, External Driver	No	4500K	3300	≥80
TL-T8-31W1800 BONT50F	Frosted 6' 31 Watt T8 Tube, External Driver	No	5000K	3350	≥80
Single End Tubes					
TL-T8-31W1800 BODS30C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	3000K	3250	≥80
TL-T8-31W1800 BODS35C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	3500K	3250	≥80
TL-T8-31W1800 BODS40C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	4000K	3300	≥80
TL-T8-31W1800 BODS45C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	4500K	3300	≥80
TL-T8-31W1800 BODS50C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	5000K	3350	≥80
Single End Tubes					
TL-T8-31W1800 BODS30F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	3000K	3250	≥80
TL-T8-31W1800 BODS35F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	3500K	3250	≥80
TL-T8-31W1800 BODS40F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	4000K	3300	≥80
TL-T8-31W1800 BODS45F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	4500K	3300	≥80
TL-T8-31W1800 BODS50F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BODT30C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	3000K	3250	≥80
TL-T8-31W1800 BODT35C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	3500K	3250	≥80
TL-T8-31W1800 BODT40C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	4000K	3300	≥80
TL-T8-31W1800 BODT45C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	4500K	3300	≥80
TL-T8-31W1800 BODT50C	Clear 6' 31 Watt T8 Tube, External Driver	Yes	5000K	3350	≥80
Two End Tubes					
TL-T8-31W1800 BODT30F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	3000K	3250	≥80
TL-T8-31W1800 BODT35F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	3500K	3250	≥80
TL-T8-31W1800 BODT40F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	4000K	3300	≥80
TL-T8-31W1800 BODT45F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	4500K	3300	≥80
TL-T8-31W1800 BODT50F	Frosted 6' 31 Watt T8 Tube, External Driver	Yes	5000K	3350	≥80