

31W 8ft TLSecond GEN T8 LED Tube

INDOOR
Linear Tube

Features and Benefits

- 31 Watt Low Power and High Performance
- Energy savings about 70%
- Unique aesthetics for commercial grade fixtures
- Excellent efficacies of up to 100 lm/W
- For Dimmable Tubes: 0-10V Dimming
- Available with internal and external drivers
- Rated Lifetime: 50,000 hours
- 5 Year Warranty*
- UV, IR and Mercury-free



5 Year Warranty

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Single End Tubes					
TL-T8-31W2400 BINS30C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	3000K	4000	≥80
TL-T8-31W2400 BINS35C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	3500K	4000	≥80
TL-T8-31W2400 BINS40C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	4000K	4250	≥80
TL-T8-31W2400 BINS45C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	4500K	4250	≥80
TL-T8-31W2400 BINS50C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	5000K	4400	≥80
Single End Tubes					
TL-T8-31W2400 BINS30F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	3000K	4000	≥80
TL-T8-31W2400 BINS35F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	3500K	4000	≥80
TL-T8-31W2400 BINS40F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	4000K	4250	≥80
TL-T8-31W2400 BINS45F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	4500K	4250	≥80
TL-T8-31W2400 BINS50F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BINT30C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	3000K	4000	≥80
TL-T8-31W2400 BINT35C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	3500K	4000	≥80
TL-T8-31W2400 BINT40C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	4000K	4250	≥80
TL-T8-31W2400 BINT45C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	4500K	4250	≥80
TL-T8-31W2400 BINT50C	Clear 8' 31 Watt T8 Tube, Internal Driver	No	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BINT30F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	3000K	4000	≥80
TL-T8-31W2400 BINT35F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	3500K	4000	≥80
TL-T8-31W2400 BINT40F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	4000K	4250	≥80
TL-T8-31W2400 BINT45F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	4500K	4250	≥80
TL-T8-31W2400 BINT50F	Frosted 8' 31 Watt T8 Tube, Internal Driver	No	5000K	4400	≥80

Applications


- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail

Voltage:	Power Factor:	Operating Temperature:	Life Hours:	Case Quantity:	Dimensions (in inches):	Indoor/Outdoor:	Certified Installer Required:
100-277 VAC	> 0.9	-10 °C to 30 °C	50,000	25 pcs	93" x 1.3"	Indoor	Yes

NOTE: Bold Part Numbers listed above are cUL



Certifications:
RoHS, FCC



*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com

31W 8ft TLSecond GEN T8LED Tube

Part Number:	Description:	Dimmable:	CCT:	Lumens:	CRI:
Single End Tubes					
TL-T8-31W2400 BONS30C	Clear 8' 31 Watt T8 Tube, External Driver	No	3000K	4000	≥80
TL-T8-31W2400 BONS35C	Clear 8' 31 Watt T8 Tube, External Driver	No	3500K	4000	≥80
TL-T8-31W2400 BONS40C	Clear 8' 31 Watt T8 Tube, External Driver	No	4000K	4250	≥80
TL-T8-31W2400 BONS45C	Clear 8' 31 Watt T8 Tube, External Driver	No	4500K	4250	≥80
TL-T8-31W2400 BONS50C	Clear 8' 31 Watt T8 Tube, External Driver	No	5000K	4400	≥80
Single End Tubes					
TL-T8-31W2400 BONS30F	Frosted 8' 31 Watt T8 Tube, External Driver	No	3000K	4000	≥80
TL-T8-31W2400 BONS35F	Frosted 8' 31 Watt T8 Tube, External Driver	No	3500K	4000	≥80
TL-T8-31W2400 BONS40F	Frosted 8' 31 Watt T8 Tube, External Driver	No	4000K	4250	≥80
TL-T8-31W2400 BONS45F	Frosted 8' 31 Watt T8 Tube, External Driver	No	4500K	4250	≥80
TL-T8-31W2400 BONS50F	Frosted 8' 31 Watt T8 Tube, External Driver	No	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BONT30C	Clear 8' 31 Watt T8 Tube, External Driver	No	3000K	4000	≥80
TL-T8-31W2400 BONT35C	Clear 8' 31 Watt T8 Tube, External Driver	No	3500K	4000	≥80
TL-T8-31W2400 BONT40C	Clear 8' 31 Watt T8 Tube, External Driver	No	4000K	4250	≥80
TL-T8-31W2400 BONT45C	Clear 8' 31 Watt T8 Tube, External Driver	No	4500K	4250	≥80
TL-T8-31W2400 BONT50C	Clear 8' 31 Watt T8 Tube, External Driver	No	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BONT30F	Frosted 8' 31 Watt T8 Tube, External Driver	No	3000K	4000	≥80
TL-T8-31W2400 BONT35F	Frosted 8' 31 Watt T8 Tube, External Driver	No	3500K	4000	≥80
TL-T8-31W2400 BONT40F	Frosted 8' 31 Watt T8 Tube, External Driver	No	4000K	4250	≥80
TL-T8-31W2400 BONT45F	Frosted 8' 31 Watt T8 Tube, External Driver	No	4500K	4250	≥80
TL-T8-31W2400 BONT50F	Frosted 8' 31 Watt T8 Tube, External Driver	No	5000K	4400	≥80
Single End Tubes					
TL-T8-31W2400 BODS30C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	3000K	4000	≥80
TL-T8-31W2400 BODS35C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	3500K	4000	≥80
TL-T8-31W2400 BODS40C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	4000K	4250	≥80
TL-T8-31W2400 BODS45C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	4500K	4250	≥80
TL-T8-31W2400 BODS50C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	5000K	4400	≥80
Single End Tubes					
TL-T8-31W2400 BODS30F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	3000K	4000	≥80
TL-T8-31W2400 BODS35F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	3500K	4000	≥80
TL-T8-31W2400 BODS40F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	4000K	4250	≥80
TL-T8-31W2400 BODS45F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	4500K	4250	≥80
TL-T8-31W2400 BODS50F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BODT30C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	3000K	4000	≥80
TL-T8-31W2400 BODT35C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	3500K	4000	≥80
TL-T8-31W2400 BODT40C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	4000K	4250	≥80
TL-T8-31W2400 BODT45C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	4500K	4250	≥80
TL-T8-31W2400 BODT50C	Clear 8' 31 Watt T8 Tube, External Driver	Yes	5000K	4400	≥80
Two End Tubes					
TL-T8-31W2400 BODT30F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	3000K	4000	≥80
TL-T8-31W2400 BODT35F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	3500K	4000	≥80
TL-T8-31W2400 BODT40F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	4000K	4250	≥80
TL-T8-31W2400 BODT45F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	4500K	4250	≥80
TL-T8-31W2400 BODT50F	Frosted 8' 31 Watt T8 Tube, External Driver	Yes	5000K	4400	≥80