

LED Explosion Proof Light with Bracket TL1

SPECIALTY
Explosion Proof Floodlight

Features and Benefits

- Durable and shock resistant
- Lens made of bulletproof PC, thermal resistant and corrosion resistant
- Low power consumption, saves energy more than 75% than traditional lighting
- Patented design for heat dissipation
- Explosion mark: Ex d II C T6
- Rated Lifetime: 50,000 hours
- 3 Year Warranty*
- UV, IR and Mercury-free



3 Year Warranty

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Wattage:	Beam Angle:	CRI:	Power Factor:	Life Hours:	Color Temperature(CCT):
TL-NB-EPL01-10W	10	140°	>70	>.90	50,000	2700-4000K, 5000-6500K
TL-NB-EPL01-15W	15	140°	>70	>.90	50,000	2700-4000K, 5000-6500K
TL-NB-EPL01-20W	20	140°	>70	>.90	50,000	2700-4000K, 5000-6500K
TL-NB-EPL01-25W	25	140°	>70	>.90	50,000	2700-4000K, 5000-6500K
TL-NB-EPL01-30W	30	140°	>70	>.90	50,000	2700-4000K, 5000-6500K

Voltage:	Frequency:	Operating Temperature:	Dimensions (in inches):	Threaded Fitting:	Installation Height:	Indoor/Outdoor:	Certified Installer Required:
220 VAC (applied for 95-265V)	50 Hz (applied for 47-63 Hz)	-30° C to +55° C	7.7" x 7.7"	G3/4"	6.5'~13'	Both	No



Applications

- Residential
- Oil Fields
- Oil Refineries
- Offshore Oil Platform
- Power Plants
- Gas Stations
- Oil Tanks
- Warf, Tunnel
- Pumping Station, Substation
- Military Base
- Zone I and II
- Hazardous Locations
- Zone 20, 21, 22
- II A, II B, II C
- Explosive Gas Atmosphere



Certifications:
RoHS Listed

*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com