

2x4 LED Troffer

INDOOR
Troffer

Features and Benefits

- 40 and 65 Watt Low Power and High Performance
- 0-10v dimming, 10%-100% smooth linear dimming
- Steel, commercial quality paint coating
- Bigger size MCPCB for better thermal management
- Replaceable LED Boards (PCBA's)
- IP Rating: IP20
- High optical grade lens
- Central lens door enables convenience of replacing PCBA's with double diffusion material, surface brightness even with a mask to prevent glare
- Rated Lifetime: Designed to L70 minimum 50,000 hours
- 5 Year Warranty*
- UV, IR and Mercury-free



Dimmable

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Wattage:	Lumens:	Dimmable:	CRI:	Voltage:	CCT:
TL-TR24-DM-40E	40	4235	Yes	≥80	120-277 VAC	4000K
TL-TR24-DM-50E	40	4235	Yes	≥80	120-277 VAC	5000K
TL-TR24-DH-40E	65	7010	Yes	≥80	120-277 VAC	4000K
TL-TR24-DH-50E	65	7010	Yes	≥80	120-277 VAC	5000K

Power Factor:	Operating Temperature:	Life Hours:	Dimensions (in inches):	Indoor/Outdoor:	Certified Installer Required:
> 0.9	-20°C to 40°C	L70 min. 50,000	47.7" x 23.8" x 3.9"	Indoor	Yes



Applications

- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail



Certifications:
RoHS



*For warranty terms please visit our website Trans-Lux.com



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com