

BR20, BR30 and BR40

INDOOR
BR / Reflector

Features and Benefits

- BR20, BR30, BR40 Low Power and High Performance
- BR lens conceals LEDs from sight and evenly distributes the light
- Smooth aluminum housing with ANSI standard form factor
- Dimmable down to ten percent
- Suitable for use in damp locations
- Not for use in enclosed luminaires
- Rated Lifetime: 25,000 hours, L70
- 5 Year Warranty*
- UV, IR and Mercury - free



BR20 BR30 BR40

Dimmable

Reduces Energy & Cost

No Lead or Mercury

Part Number:	Replaces:	Wattage:	Lumens:	CRI:	CCT:	Dimensions (in inches):	Energy Star Rated:
BR20							
TL7BR20DLED27	50W	7	550	80	2700K	3.8" x 2.5"	★
TL7BR20DLED30	50W	7	550	80	3000K	3.8" x 2.5"	★
TL7BR20DLED41	50W	7	550	80	4100K	3.8" x 2.5"	
BR30							
TLHC8BR30DLED27-RB4	65W	8	650	80	2700K	5" x 3.7"	★ †
TL11BR30DLED27	65W	11	850	80	2700K	5" x 3.7"	★
TL11BR30DLED30	65W	11	850	80	3000K	5" x 3.7"	★
TL11BR30DLED41	65W	11	850	80	4100K	5" x 3.7"	
BR40							
TL17BR40DLED27	100W	17	1400	80	2700K	6.2" x 4.7"	★
TL17BR40DLED30	100W	17	1400	80	3000K	6.2" x 4.7"	★
TL17BR40DLED41	100W	17	1400	80	4100K	6.2" x 4.7"	
90 CRI LAMPS							
BR30							
TL14BR30DLED930	75W	14	800	90	3000K	5" x 3.7"	★
BR40							
TL14BR40DLED930	75W	14	1000	90	3000K	6.2" x 4.7"	

† = Available in 4 pack only

Power Factor:	Operating Voltage:	Operating Frequency:	Operating Temperature:	Life Hours:	Indoor/Outdoor:	Certified Installer Required:
>0.90	120V	60 Hz	-20 °C to 40 °C	25,000	Indoor	No

Compatible Dimmers

Make	Dimmer Model
Lutron	CTCL-153P
Lutron	DVCL-153P
Lutron	LGCL-153P
Lutron	S-600
Leviton	IPL06
Leviton	IPI10
Leviton	6631-LW
Leviton	6683-IW

Applications

- Indoor recessed can
- High hat
- Ceiling mounted strip lighting
- Residential
- Office
- Retail
- Restaurant
- School
- Hospital
- Hotel/Motel

Certifications:
RoHS, FCC

TLENERGY
by **TRANS LUX**

Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com