

Horizontal Mount 15W - 2G11

INDOOR
2G11

Features and Benefits

- 15 Watt Low Power and High Performance
- Driver: Constant Current/Isolated
- Driver Box: Isolated from Heat Sink
- Cover: Frosted or Clear
- Testing Reports: LM79, LM80 available
- Rated Lifetime: 50,000 hours
- 3 Year Warranty*
- High quality built-in drivers: PFC>0.91, Harmonic wave <9%, ripple wave <9%
- UV, IR and Mercury-free
- UL/CUL – Damp and Dry Locations



Rated Life
50,000 hours

Reduces
Energy & Cost

Savings up to
60%

Part Number:	Replaces:	Wattage:	Base		Lumens:	CRI:	Beam Angle:	Color Temperature(CCTK):
			Type(s):	Lens				
GI-2G11-1-C-15W 3K	32W	15	2G11	Clear	1350~1500	>83	120°	3000K
GI-2G11-1-C-15W 41K	32W	15	2G11	Clear	1350~1500	>83	120°	4100K
GI-2G11-1-C-15W 6K	32W	15	2G11	Clear	1350~1500	>83	120°	6000K
GI-2G11-1-F-15W 3K	32W	15	2G11	Frosted	1350~1500	>83	120°	3000K
GI-2G11-1-F-15W 41K	32W	15	2G11	Frosted	1350~1500	>83	120°	4100K
GI-2G11-1-F-15W 6K	32W	15	2G11	Frosted	1350~1500	>83	120°	6000K

Voltage:	Operating		Dimensions (in feet):	Indoor/Outdoor:	Certified Installer Required:
	Frequency:	Life Hours:			
100-277V	50-60 Hz	50,000	1.34 ft	Both	Yes



Applications

- Office
- Wall Sconce
- Desk Lamp
- Retail
- Restaurant
- School
- Hospital
- Hotel/Motel



Certifications:
RoHS

0070



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com