Horizontal Mount 20W - 2G11

Features and Benefits

- 20 Watt Low Power and High Performance
- Driver: Constant Current/Isolated
- Driver Box: Isolated from Heat Sink
- Cover: Frosted or Clear
- Testing Reports: LM79, LM80 available
- Rated Lifetime: 50,000 hours
- 3 Year Warranty*
- High quality bulit-in drivers: PFC>0.91, Harmonic wave <9%, ripple wave <9%
- UV, IR and Mercury–free
- UL/CUL – Damp and Dry Locations

Rated Life 50,000 hours

Reduces Energy & Cost

Savings up to 60%

Part Number:	Replaces:	Wattage:	Base Type(s):	Lens	Lumens:	CRI:	Beam Angle:	Color Temperature(CCTK):
GI-2G11-2-C-20W 3K	40W	20	2G11	Clear	1800~2000	>83	120°	3000K
GI-2G11-2-C-20W 41K	40W	20	2G11	Clear	1800~2000	>83	120°	4100K
GI-2G11-2-C-20W 6K	40W	20	2G11	Clear	1800~2000	>83	120°	6000K
GI-2G11-2-F-20W 3K	40W	20	2G11	Frosted	1800~2000	>83	120°	3000K
GI-2G11-2-F-20W 41K	40W	20	2G11	Frosted	1800~2000	>83	120°	4100K
GI-2G11-2-F-20W 6K	40W	20	2G11	Frosted	1800~2000	>83	120°	6000K

Voltage:	Operating Frequency:	Life Hours:	Dimensions (in feet):	Indoor/ Outdoor:	Certified Installer Required:
100-277V	50-60 Hz	50,000	1.75 ft	Both	Yes

Applications

- Office
- Wall Sconce
- Desk Lamp
- Retail
- Restaurant
- School
- Hospital
- Hotel/Motel

Certifications:
RoHS

0071

TLENERGY by TRANSLUX
Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com