TLENERGY LED LIGHTING

Industrial Highbay Premium

Features and Benefits

- Highly efficient LEDs provide up to 98 lumens per watt at 70 CRI
- Individual optics for each LED allow for precise control of light distribution
- Operates in ambient temperatures from 45° C/113°F down to -40° C/ -40° F (0°C/32°F with Occupancy Sensor)
- Long-life, LEDs at L80 reduce life cycle maintenance costs
- One or two module packages available
- Compact size
- Fixed or dimming output options
- Rated life 50,000 hours
- UV, IR and Mercury-free
- UL-Dry Location



Rated Life 50,000 hours

Reduces Energy & Cost

No Lead or Mercury

| Part Number: | Wattage: CF | | CRI: Lumens: | Life Hours: | Color Temperature(CCTK): | Voltage: |
|--------------------------|-------------|----|--------------|-------------|-----------------------------|-------------|
| TL LLHP2-50H-M-EDU-F3C10 | 281 | 70 | 13000 | 50,000 | 5000K | 120-277 VAC |

| | Operating Temperature: | Dimensions (in inches): | Indoor/ Outdoor: | Certified Installer Required: |
|------|---------------------------|----------------------------------|---------------------|-------------------------------|
| >0.9 | -20°C to 60°C | L 24.313" x W 11.375" x H 9.125" | Indoor | Yes |

Applications

- Highbay
- Lowbay
- Industrial





