

PAR20, PAR30, PAR38 Dimmable

Features and Benefits

- PAR20, PAR30, PAR38 Low Power and High Performance
- Fully dimmable, brilliant LED light
- Dimmable
- Life Rating is based on 70% Lumen Maintenance
- Excellent white color consistency from bulb to bulb
- Rated life 25,000 hours
- UV, IR and Mercury-free
- UL-Damp and Dry Locations

Dimmable

Reduces Energy & Cost

No Lead or Mercury



PAR20

PAR30

PAR38

Lamp Type:	Part Number:	Wattage:	CBCP:	CRI:	Lumens:	Beam Angle:	Power Factor:	Dimensions (in inches):	Color Temperature(CCTK):
PAR20	TL-P208E2627KSPFL	8	757	80	500	25°	0.95	2.5" x 3.7"	2700K
PAR20	TL-P208E2630KSPFL	8	757	80	500	25°	0.95	2.5" x 3.7"	3000K
PAR30	TL-P312E2627KCRFL	12	1552	80	800	40°	0.89	4.5" x 3.7"	2700K
PAR30	TL-P312E2630KCRFL	12	1552	80	800	40°	0.89	4.5" x 3.7"	3000K
PAR30	TL-P313E2627KSPFL	13	1792	80	800	25°	0.95	4.5" x 3.7"	2700K
PAR30	TL-P313E2630KSPFL	13	1792	80	800	25°	0.95	4.5" x 3.7"	3000K
PAR38	TL-P417E2630KSPFL	17	2488	80	1200	25°	0.97	4.6" x 5.1"	3000K
PAR38	TL-P417E2640KSPFL	17	2488	80	1200	25°	0.97	4.6" x 5.1"	4000K
PAR38	TL-P417E2627KCRFL	17	2305	80	1200	40°	0.9	4.6" x 5.1"	2700K
PAR38	TL-P417E2630KCRFL	17	2305	80	1200	40°	0.9	4.6" x 5.1"	3000K
PAR38	TL-P417E2640KCRFL	17	2305	80	1200	40°	0.9	4.6" x 5.1"	4000K

Voltage:	Operating Frequency:	Operating Temperature:	Life Hours:	Indoor/Outdoor:	Certified Installer Required:
120 VAC	60 Hz	-20°C to 40°C	25,000	Indoor	Yes

Applications

- Track Lights
- Recessed Downlights
- Display Lights
- Outdoor Fixtures that Protect Lamps from Elements



PAR20

PAR30

PAR38



Certifications:
RoHS



Trans-Lux Energy Corporation
300 N Elizabeth St Suite 610c
Chicago, IL 60607
800.559.8197 • www.Trans-Lux.com